

Select the level of protection your RV needs.

30A  
Portable  
44740



30A  
Portable  
AECM  
10086



30A  
Portable  
with LCD  
34730



30A  
Hardwire  
34520



50A  
Portable  
with LCD  
34750



50A  
Hardwire  
34560



50A  
Hardwire  
40240



Over/Under Voltage			●	●	●	●	●
Open Neutral Protection			●	●	●	●	●
Reverse Polarity Protection			●	●	●	●	●
Miswired Pedestal Indication		●	●	●	●	●	●
Ground Fault Protection	●						
Dangerous Current on Ground Wire Indication			●	●	●	●	
Time Delay at Power Up (2 min. 15 sec.)			●	●	●	●	●
Remote LCD Display				Optional		Optional	●
Built-In LCD Display			●		●		
Weather Resistant	●	●	●		●		
UL Listed				●		●	●
Source Power Connection Diagnostics							●
Lock Hasp Available	●		●		●		
Cord Gauge	10/3	N/A	10/3	N/A	6/4	N/A	N/A
Electrical Rating	120V, 30A	120V, 30A	120V, 30A	120V, 30A	120/240V 50A	120/240V 50A	120/240V 50A
Surge Suppression (Joules)	510	1,020	2,450	2,450	3,850	3,850	3,350
Max Spike Current	1,250A	N/A	6,500A	6,500A	6,500A	6,500A	130,000A

Select the level of protection your RV needs.

50A  
Basic ATS  
40100



50A  
Limited Protection  
41260



50A  
Full Protection  
40250-RVC



90A  
Full Protection  
41290-RVC



	50A Basic ATS 40100	50A Limited Protection 41260	50A Full Protection 40250-RVC	90A Full Protection 41290-RVC
Over/Under Voltage			●	●
Open Neutral Protection		●	●	●
Reverse Polarity Protection		●	●	●
Miswired Pedestal Indication			●	●
Ground Monitoring			●	●
Time Delay at Power Up	●	●	●	●
Remote Display (Optional)			●	●
Amperage Measurement			●	●
Third Party Listed	●	●	●	
Source Power Connection Diagnostics			●	●
Generator Dominant	●	●	●	●
Mechanical Interlocking Contactors	●	●	●	●
Electrical Rating	120/240V, 50A	120/240V, 50A	120/240V, 50A	120/240V, 90A
Surge Suppression (Joules)	N/A	2,600	3,350	3,350
Max Spike Current	N/A	76,400A	130,000A	130,000A
Contactor Rating	50A, FLA	50A, FLA	65A, FLA	95A, FLA
UL Standard	UL 1008	UL 1008	UL 1008	UL 1008

